

Product features

High cost performance semi flexible cable components.


Main specifications

Items	Frequency (G)	Min	Type	Max	Units
Frequency		DC	~	18	GHz
IL	DC-18		0.79	0.84	dB
VSWR	DC-18		1.20	1.25	dB

Other parameters

Cable category	Hand-Flex Cable
Length	150mm
Connector 1	SMA-M Stainless steel
Connector 2	SMA-K
Impedance	50Ω
Operation Temp.	-40~+85°C Design assurance
Storage Temp.	-40~+85°C Design assurance

Configuration



Overall dimensions (mm)

A	150	mm	E1	8.0	mm
B	4.2	mm	W1	8.9	mm
T	2	mm			


Reference picture



Typical test data


频率(MHz)	IL	Input VSWR	Output VSWR
10	0.05	1.02	1.01
1000	0.15	1.02	1.02
2000	0.24	1.03	1.02
3000	0.28	1.03	1.04
4000	0.33	1.04	1.03
5000	0.36	1.04	1.03
6000	0.37	1.04	1.05
7000	0.42	1.05	1.05
8000	0.45	1.07	1.04
9000	0.47	1.1	1.07
10000	0.5	1.09	1.11
11000	0.53	1.12	1.1
12000	0.58	1.12	1.11
13000	0.63	1.13	1.12
14000	0.73	1.09	1.1
15000	0.74	1.12	1.13
16000	0.77	1.11	1.11
17000	0.79	1.13	1.14
18000	0.81	1.16	1.14

Typical test curve




Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.

Type power curve



Cable structure diagram



Note

- | | |
|---|---|
| 1 | Suggested installation radius greater than 10mm |
|---|---|