

Product features

High cost performance, armored stable amplitude and phase cable.


Main specifications

Items	Frequency (G)	Min	Type	Max	Units
Frequency		DC	~	50	GHz
IL	DC-50			3.9	dB
VSWR	DC-50			1.35	

Other parameters

Cable category	Armored stable amplitude and phase
Length	1000mm
Connector 1	2.4-K
Connector 2	2.4-K
Impedance	50Ω
Operation Temp.	-40~+85°C Design assurance
Storage Temp.	-40~+85°C Design assurance

Configuration



Overall dimensions (mm)

A	1000	mm
B	6.3	mm
T	13	mm

Reference picture




Typical test data


F (MHz)	IL (dB)	Input VSWR	Output VSWR
100	0.01	1.01	1.01
1000	0.02	1.02	1.02
4000	0.41	1.04	1.03
6000	0.55	1.04	1.05
8000	0.66	1.05	1.05
10000	0.92	1.06	1.06
15000	1.1	1.06	1.05
18000	1.36	1.05	1.06
20000	1.42	1.06	1.07
26500	1.89	1.08	1.09
30000	2.32	1.10	1.10
40000	3.12	1.11	1.14
50000	3.87	1.15	1.17

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.


Type power curve



Typical test curve



Cable structure diagram



Note

- 1 Installation radius greater than 80mm