

Main specifications

Items	Frequency (G)	Min	Type	Max	Units
Frequency		DC	~	67	GHz
IL			3.0	3.5	dB
VSWR			1.2	1.35	



Reference picture




Other parameters

Cable category	LL Phase Stable
Length	300mm
Connector 1	1.85-M or J
Connector 2	1.85-M or J
Impedance	50Ω
Operation Temp.	-40~+85°C Design assurance
Storage Temp.	-40~+85°C Design assurance
Quality Grade	Industrial grade
ROHS	符合

Typical test curve




Configuration




Overall dimensions (mm)

A	300	mm	C1	8	mm
B	2.2	mm	E1	8	mm
T	20	mm	W1/W2	8.9	mm

Type power curve



Cable structure diagram



Note

Static turning radius	12mm
Dynamic conversion to radius	22mm

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.

Typical test data

Frequency GHz	S11 VSWR	S22 VSWR	S12 IL dB
0.01	1.01	1.01	-0.02
4.79	1.05	1.07	-0.55
9.57	1.07	1.02	-0.92
14.36	1.07	1.11	-1.23
19.14	1.03	1.07	-1.39
23.93	1.05	1.02	-1.53
28.71	1.04	1.05	-1.73
33.50	1.12	1.10	-1.89
38.29	1.10	1.15	-2.17
43.07	1.06	1.09	-2.30
47.86	1.11	1.15	-2.52
52.64	1.02	1.11	-2.64
57.43	1.13	1.03	-2.78
62.21	1.11	1.02	-2.93
67.00	1.09	1.17	-2.99

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.