

COM-MW TECHNOLOGY

"\r\n
\r\n
\r\n
\r\n\r\n
\r\n

Waveguide Connection DWG8-BJ100S100-2825

Frequency	Power	Loss	Reflection	Bandwidth
12.5-13.5 GHz	~8.2 W	~0.2 dB	~12.5%	12.5-13.5 GHz
13.5-14.5 GHz	~8.2 W	~0.2 dB	~12.5%	13.5-14.5 GHz

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.

COM-MW TECHNOLOGY

\u53c2\u6570</th>\r\n	\u6700\u5c0f</th>\r\n	\u5178\u578b</th>\r\n	\u6700\u5927</th>\r\n	\u5355\u4f4d</th>\r\n</tr>\r\n</thead>\r\n</table><table><tr><th>\u9891\u7387 GHz</th><th>S11 \u9a7b\u6ce2</th><th>S22 \u9a7b\u6ce2</th><th>S12 \u635f\u8017 dB</th></tr><tr><td>12.5</td><td>1.01</td><td>1.03</td><td>-0.04</td></tr></tbody></table><div>\r\n\r\n</div>\r\n\r\n\r\n\r\n</p></div><div>\u5178\u578b\u6d4b\u8bd5\u66f2\u7ebf\u56fe</h3></div>\r\n</div>\r\n</div>\r\n</div></table>
-----------------------	-----------------------	-----------------------	-----------------------	--

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.