


COM-MW TECHNOLOGY

"\r\n
\r\n
\r\n
\r\n

Component ZS8-C1950-2550-2724

Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm
Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm
Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm
Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm
Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm
Frequency 1950~2550 MHz	Power 0.4~1.4 W	Efficiency 49.5~50.5 %	Bandwidth 60 MHz	Modulation QPSK, 16QAM, 64QAM	Carrier Frequency Tolerance ±0.001 %	Spurious Emission ≤ -30 dBm

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.



\u65b9\u5411\u6027</td>	</td>	</td>	15</td>	</td>	</td>	</td></tr></tbody></table></div> <h3>\u5176\u5bb3\u53c2\u6570</h3><table><tr><td>\u63a5\u53e3\u5f62\u5f0f</td><td>N -K</td></tr><tr><td>\u8868\u9762</td><td>\u672c\u5bfc</td></tr><tr><td>\u529f\u7387\u5bb9\u91cf</td><td>800W\u8bbe\u8ba1\u4fdd\u8bc1</td></tr><tr><td>\u4ea7\u54c1\u5916\u58f3\u6750\u6599</td><td>\u94dd6061</td></tr><tr><td>\u5de5\u4f5c\u6e29\u5ea6</td><td>-40~+70\u2103\u8bbe\u8ba1\u4fdd\u8bc1</td></tr></table></h3>
-------------------------	-------	-------	---------	-------	-------	--

Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.

