

Product features

Small size, high cost-effectiveness.

Main specifications

Parameters	Frequency	/	Min	Typical	Max	Units
Passband			DC	~	550	MHz
Passband IL					1.0	dB
Rejection	800-1050	MHz $\geq$	20			dB
Rejection	1050-2000	MHz $\geq$	35			dB
Passband VSWR				1.2		


Other parameters

Connector	SMD
Impedance	50 Ω
Power	0.5W Design assurance
Work Temp.	-40~+85°C Design assurance
Storage Temp.	-55~+100°C Design assurance
Quality Grade	Industrial grade
Other	-3dB cutoff frequency 605MHz; Replacing SXLP-550+


Port Definition

I/O Port	1,8
GND	2, 3, 4, 5,6,7



Functional diagram




Reference picture



Configuration(mm)



Typical test curve



Note: The specifications and performance data contained in this data sheet are based on tests established by CMW.

Typical test data

Frequency(MHz)	S11 VSWR	S22 VSWR	S12 IL dB	S12 Delay nS
0.01	1.01	1.01	-0.05	1.48
57	1.01	1.01	-0.05	1.48
114	1.11	1.11	-0.11	1.54
171	1.11	1.11	-0.13	1.57
229	1.09	1.08	-0.14	1.63
286	1.03	1.03	-0.17	1.7
343	1.04	1.06	-0.21	1.81
400	1.07	1.1	-0.24	1.93
457	1.08	1.1	-0.3	2.13
514	1.14	1.13	-0.41	3.3
571	1.07	1.08	-0.51	3.91
629	2.29	2.32	-1.51	2.7
686	9.29	9.38	-6.72	1.35
743	25.3	23.54	-13.22	1.16
800	42.03	39.14	-20.93	1.2

Note

1	Please do not wash the product in the cleaning solution.,Please do not wash the product in the cleaning solution.
2	The product supports 190 °C reflow soldering